

#Jenny



Finally I get this ebook, thanks for all these I can get now!

#Rio



Cool! I'am really happy

#Markus Jensen



I did not think that this would work, my best friend showed me this website, and it does! I get my most wanted eBook

#Hun Tsu



wtf this great ebook for free?!

#Che Salsa



My friends are so mad that they do not know how I have all the high quality ebook which they do not!

#Diego Butler




so many fake sites. this is the first one which worked! Many thanks


Gudgeon/Gudgeon Spindle

REPLACE GUDGEON SPINDLE

1. Remove gudgeon driveline. (See Remove Gudgeon Driveline, this Group).
2. Disconnect SCV control cables. Disconnect lines as necessary. Route cables and lines to large area. Remove sheet metal as necessary.
3. Disconnect rear electrical outlet from SCV. Remove manual switch from rear fender. Disconnect all wiring harnesses. Route harnesses forward to large area.
4. Connect lifting straps and/or chains to the rear frame assembly and an overhead hoist. Be sure to connect strap/chains so the frame will be balanced during removal. Take slack out of strap/chains.




5. Leave stand (B) under gudgeon and remove gudgeon oscillation stop (A).



6. Remove three strut cap retainer screws.

7. Install J00059 Oscillation Spindle Cap Tool (A) and remove strut cap.

8. Carefully move rear frame assembly from gudgeon.



TM1433 (10.03.01) 80-10-15 85-87-8960 Tractors Repair www.epcatalogn.com

[Download PDF version of :](#)
8760 John Deere Service Manual